



RADIAL BALL BEARINGS

INCH MINI 440C STAINLESS "R" SERIES



ZZ



2RS



Bore in d	OD in D	Width (ZZ or 2RS) W in	Width (Open) W in	Bearing Number	Basic Load Rating Pounds		Speed Rating		Weight (lb)
					Dynamic	Static	Grease RPM	Oil RPM	
0.1250	0.375	0.1560	0.1562	SSR2	144	50	49000	58000	0.003
0.1875	0.500	0.1960	0.1562	SSR3	295	110	41000	48000	0.005
0.2500	0.625	0.1960	0.1960	SSR4	335	139	44000	54000	0.010
0.2500	0.750	0.2810	0.2188	SSR4A	525	200	39000	48000	0.017
0.3750	0.875	0.2810	0.2188	SSR6	745	315	31000	38000	0.024
0.5000	1.250	0.3120	0.2500	SSR8	1148	535	24000	29000	0.039
0.6250	1.375	0.3440	0.2812	SSR10	1347	734	18000	22000	0.081

* Cages and shields are constructed of 304 stainless.

INCH MINI "INSTRUMENT TYPE" 440C STAINLESS

Bore in d	OD in D	Width in W	Bearing Number	Basic Load Rating Pounds		Speed Rating Grease RPM	Weight (lb)
				Dynamic	Static		
0.0937	0.1875	0.0625	SSRI3332ZZ	28	9	73000	0.001
0.1250	0.2500	0.0937	SSRI418ZZ	64	22	59000	0.001
0.1250	0.3125	0.1094	SSRI518ZZ	126	40	54000	0.002
0.1250	0.3750	0.1094	SSRI618ZZ	144	51	49000	0.002
0.1562	0.3125	0.1094	SSRI5532ZZ	75	30	51000	0.001
0.1875	0.3125	0.1094	SSRI5632ZZ	85	30	49000	0.001
0.1875	0.3750	0.1250	SSRI6632ZZ	160	60	46000	0.002
0.2500	0.3750	0.1250	SSRI614ZZ	45	22	43000	0.002
0.2500	0.5000	0.1250	SSRI814ZZ	185	80	39000	0.004
0.3125	0.5000	0.5620	SSRI8516ZZ	121	62	40000	0.003
0.3750	0.6250	0.1560	SSRI1038ZZ	96	53	30000	0.006
0.5000	0.7500	0.1560	SSRI1212ZZ	111	71	24000	0.007

* Instrument type stocked as ZZ only. 2RS or LL (Teflon seals) may be available. Contact factory.
Also available in ABEC 3 & 5 precision. Contact factory.

